



**SURPASS
 EXPECTATIONS
 BEYOND
 VALUES.**

Get the most value for your money with Epson business projectors! These projectors are designed to be your choice regardless if they are used in a corporate setting or in the educational field. With your convenience in mind, you can now project your content wirelessly from compatible smart devices without any additional software installation. Now you are able to showcase your content crisp and clear on large screens.



EB-FH52



12,000 Hours
 Lamp Life in
 Eco Mode



Split
 Screen



Auto
 Vertical
 Keystone



Horizontal
 Keystone
 Slider



iProjection



Cost
 Effective



IT'S IN THE DETAILS.

3LCD technology that delivers quality projected images and reliable performance.

MODEL NUMBER	EB-FH52	
Projection Technology	RGB liquid crystal shutter projection system (3LCD)	
Specifications of Main Parts		
LCD	Size	0.61" (C2fine)
	Native Resolution	1080p
Lightsource	Type	230W UHE
	Life (Normal / Eco)	5,500 / 12,000 hours
	Aspect Ratio	16:9
Projection Lens	Type	Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.51 – 1.99
	Focal Length	18.20 – 29.20 mm
	Zoom Ratio	1 – 1.6
	Throw Ratio	1.32 – 2.14 (Wide to Tele)
Screen Size (Projected Distance)		
Standard	Tele: 30" to 300" [1.42 to 14.41 m]	
	Wide: 30" to 300" [0.87 to 8.88 m]	
Brightness¹		
White Light Output (Normal / Extended)	4,000 lm	
Colour Light Output	4,000 lm	
Contrast Ratio	16,000:1	
Geometric Correction		
Vertical / Horizontal Keystone	±30° / ±30° (Auto Vertical Keystone only)	
Quick Corner	Yes	
Split Screen	Yes	
Internal Speakers	Monoaural: 16W x 1	
Connectivity		
Analog Input	D-Sub 15Pin	1
	Composite	1 (RCA)
	Digital Input	NA
Digital Input	HDMI	2
	HDBaseT	NA
	Output Terminal	NA
Audio Input	D-Sub 15Pin	NA
	HDMI	NA
Audio Output	2RCA (White & Red)	1
Others	Stereo Mini Jack	NA
	USB Type A	1 (For Wireless LAN, Firmware Update, Copy OSD Settings)
Control I/O	USB Type B	1 (For Firmware Update, Copy OSD Settings)
	RS-232C	NA
Network	Remote Control Input	NA
	Wired LAN	NA
	Wireless	Built-In
Wireless Specification (Screen Mirroring)		
Supported Speed For Each Mode	IEEE 802.11g (2.4GHz): 54Mbps ² / IEEE 802.11n (2.4GHz): 130 Mbps ² / IEEE 802.11a (5GHz): 54 Mbps ² / IEEE 802.11n (5GHz): 270 Mbps ² / IEEE 802.11ac (5 GHz): 780 Mbps ²	
Wireless Specification (Built-in Wireless LAN)		
Supported Speed For Each Mode	IEEE 802.11b (2.4GHz): 11Mbps ² / IEEE 802.11g (2.4GHz): 54 Mbps ² / IEEE 802.11n (2.4GHz): 72.2 Mbps ² / IEEE 802.11a (5GHz): 54 Mbps ² / IEEE 802.11n (5 GHz): 150 Mbps ²	
Wireless LAN Security	Quick Mode: OPEN, WPA2-PSK (AES) Advanced Mode: OPEN, WPA2/WPA3-PSK, WPA2/WPA3-EAP Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast	
Operating Temperature		
	Low Altitude: 5 – 40 °C <41 – 104 °F> High Altitude: 5 – 35 °C <41 – 95 °F> (20% – 80% Humidity, No Condensation)	
Operating Altitude		
	0 – 3,048 m <0 – 10,000 ft>	
Direct Power On / Off		
	Yes	
Start-Up Period		
	Up to 6 seconds, Warm-up Period: 30 seconds	
Cool Down Period		
	Instant Off	
Air Filter		
Type	High Efficiency Filter	
Maintenance Cycle (Normal / Eco)	10,000 / 20,000 hours ³	
Power Supply Voltage		
	100 – 240 V AC ±10%, 50/60 Hz	
Power Consumption (220 - 240V)		
Lamp (Normal / Eco)	327W / 225W	
Standby (Network / Energy Saving)	2.0W / 0.3W	
Dimension Excluding Feet (D X W X H)		
	282 x 309 x 90 mm	
Weight (Including Standard Lens)		
	Approx. 3.1 kg	
Fan Noise (Normal / Quiet)		
	37dB / 28dB	

¹ Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

² Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

³ When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m³). Based on the Epson's in-house test results.

EB-FH52

Supplied Accessories

Power Cable (1.8m)
Connection Cable (1.8m)
Remote control with 2AA Battery
ELPAP11 Wireless Lan (Built-In)
User's Manual CDROM
Quick Start Guide
Soft Carry Case

Optional Accessories

Spare Lamp: ELP97
Air Filter: ELPAF54
Ceiling Mount: ELPMB23



EB-FH52

©2020 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.
Printed September 2020

Sales Enquiries
800 120 5564

EpsonSingapore @epsonsingapore EpsonSoutheastAsia Epson Singapore

For latest specifications, visit www.epson.com.sg/projectors or call **800 120 5564**.

Epson Singapore Pte Ltd
Epson Customer Care Center

438B Alexandra Road, Block B Alexandra Technopark, #04-01/04, Singapore 119968. Tel: (65) 6586-5500
100G Pasir Panjang Road, #01-09 Interlocal Centre, Singapore 118523. Epson Helpdesk: 800 120 5564. Opening hours: Monday - Friday, 9am to 5pm.
Closed on Saturday, Sunday and Public Holiday. Please refer to www.epson.com.sg/contact for updated opening hours.